



Bradford
enviroseal™

ENVIROSEAL™

YOUR ARMOUR AGAINST THE ELEMENTS



Protect your investment and your worksite



Wrapping a home with Bradford EnviroSeal once the frame is up is a vital element in protecting your investment and the safety of the worksite during the building process.

EnviroSeal acts as a physical barrier to weather as well as guarding the interior of the home from condensation and extreme temperature variations. This added protection allows you to continue work safely inside the home, even before the exterior cladding is installed.

Once construction is completed, EnviroSeal acts as a second skin, helping to weatherise the home. This makes it more energy efficient and comfortable for the homeowner.



Enjoy all the benefits of EnviroSeal

- Improves worksite safety
- Provides ongoing physical protection against the elements
- Maintains work flow and cash flow
- Reduces temperature variations and condensation
- Provides additional security
- Improves homeowner comfort by weatherising the home

Worker protection

EnviroSeal improves the working environment and provides additional insurance against personal injury. It helps minimise the risk of slip injuries by keeping out rain and condensation so that the internal environment stays dry.

EnviroSeal also effectively keeps out wind and draughts from the home, reducing the risk of dust related injuries.

Physical Protection

EnviroSeal Wall Wrap and Roof Sarking provide continuous protection from rain, wind and dust to the interior of the home and the materials and people in it.

They are constructed from an incredibly tough combination of woven polymer with an aluminium foil facing for increased impermeability and thermal performance.

EnviroSeal Roof Safety has been rigorously tested and can be used without fall arrest mesh on 600mm spans. It is also certified as resistant to hail.

EnviroSeal Wall Wrap has been designed to withstand exposure to the elements for up to two months, shielding the frame from getting wet which can lead to the leaching of the timbers natural protective tannins and cause rot over time.

Workflow and cash flow protection

By locking out the elements you can keep working on fitting out the interior even while you're waiting for the exterior cladding to be completed. This can save weeks off the building schedule, allowing the homeowner to take possession sooner, and you get those final payments quicker.



Thermal and condensation protection

EnviroSeal's reflective foil surface provides thermal insulation, reducing the extremes of temperature within the home to make it a more comfortable place to work and live.

It also reduces the potential effects of condensation which can be trapped in the structure and cause mould and fungus growth. This often only becomes evident after construction and can be expensive to rectify.

Site protection

EnviroSeal Wall Wrap enhances your work site security by providing a visual barrier. It keeps materials and equipment safe from prying eyes.





Added protection for homeowners

By protecting a house with EnviroSeal you are effectively adding a second skin to the whole home, locking out moisture and unwanted draughts. This improves energy efficiency and reduces the potential for rot and mould which can effect allergy sufferers and damage the structure.

By including EnviroSeal you are providing a quality home and a better and healthier environment for your customers.

The EnviroSeal range

The complete range of EnviroSeal Wall and Roof foil insulation ensures you always have the right product for every need.



Product specifications

Product	Purpose and Benefit	Dimensions		m ² per Roll	Rolls per Pallet	Product Code
		Width (mm)	Length (m)			
EnviroSeal Roof Metal/Wall	<ul style="list-style-type: none"> Economical Domestic wall application or under metal roofing Keeps out moisture, wind and dust 	1,350 mm	20 m	27 m ²	50	30388
		1,350 mm	60 m	81 m ²	50	15056
EnviroSeal Wall Wrap	<ul style="list-style-type: none"> Light weight Tear resistant Keeps out moisture, wind and dust 	1,350 mm	20 m	27 m ²	50	15127
		1,350 mm	60 m	81 m ²	50	15128
EnviroSeal Wall Breather	<ul style="list-style-type: none"> Permeable membrane designed for cladding Light weight Tear resistant 	1,350 mm	20 m	27 m ²	50	15122
		1,350 mm	60 m	81 m ²	50	15123
EnviroSeal Roof Tile	<ul style="list-style-type: none"> Ideal for under tiled roofs Pliable, strong and easy to use Ideal for coastal areas 	1,500 mm	30 m	45 m ²	50	15110
EnviroSeal Roof Tile Plus	<ul style="list-style-type: none"> Higher weight and rigidity makes this the easiest foil to install Superior tensile strength Tear resistant 	1,500 mm	30 m	45 m ²	50	27308
EnviroSeal Roof Tile Safety	<ul style="list-style-type: none"> Fall protection, meets AS/NZS 4040.4 (modified) certified by AFIMA Ultimate protection against the elements Does not require safety mesh for spans of 600mm 	1,500 mm	30 m	45 m ²	50	27060

For further information contact CSR Bradford Insulation on 1300 850 305 or visit www.bradfordinsulation.com.au.



CSR Bradford Insulation
55 Stennett Rd
Ingleburn NSW 2565 Australia
Telephone (02) 9765 7000 Facsimile (02) 9765 7002

CSR Bradford Insulation is a business division of CSR Building Products Limited ABN 55 008 631 356

