


ENVIROSEAL™ ROOF TILE



General Description

Bradford Enviroseal™ Roof Tile is an economical, pliable sarking foil that is ideal for use under cement and terracotta tiled roof, however is not suitable for use under metal deck and slate tile roofing.

Product Description

Bradford Enviroseal Roof Tile is a pliable heavy duty sarking foil with a high tensile strength and tear resistance. Roof Tile is a radiant barrier consisting of reinforced, aluminium foil laminated with fire retardant adhesive to a high tensile and tear strength woven polymeric fabric. It is suitable for use in bush fire prone areas and has a green backing to eliminate glare during installation.

Applications

Bradford Enviroseal Roof Tile is a pliable foil insulation with high tensile strength and tear resistance designed for use as sarking under cement and terracotta tiled roofs. Enviroseal Roof Tile provides protection against dirt, dust, draughts whilst contributing thermal insulation properties to keep homes warmer in winter and cooler in summer. Additionally, the installation of Enviroseal™ Roof Tile will add to the overall thermal performance of the roof when a clear airspace of at least 20mm or more is provided at the reflective side of the foil face. Reducing glare from

the external face of a building is an important site construction and road safety requirement. Enviroseal Roof Tile has a green backing which is installed to the outside of the building to reduce reflection to acceptable levels.

Benefits

- Pliable, strong and easy to use
- Ideal for under cement and terracotta tiled roof
- Provides ongoing physical protection against the elements
- Reduces temperature variations and wind driven rain water inside the home
- Protects your home from burning amber generated from a bushfire
- Provides additional security from inclement weather
- Can be used for coastal areas; and
- Improves homeowner comfort by weatherising the home

Health & Safety

Information on any known health risks on our products and how to handle them safely is detailed on our website www.bradfordinsulation.com.au. Additional information is listed in the Material Safety Data Sheets also available on our website.

Standard Sizes & Packaging

Width(mm)	Length(m)	m ² per roll	Rolls per pallet	Product code
1500	30	45	50	15110

Durability


Bradford Enviroseal Roof Tile is a general purpose Roof Sarking product and is guaranteed to be free from manufacturing defects. Bradford Enviroseal Roof Tile will perform in normal building applications when installed in accordance with AS/NZS 4200.2:1994 Pliable Building Membranes and Underlay's, Part 2 Installation Requirements and any special notes detailed in this data sheet or those found in Bradfords design guide documents. Please note, all work must be designed and constructed in compliance with all provisions of the current Building Code of Australia, regulations and relevant standards. Being a secondary sarking material, Bradford Enviroseal Roof Tile is not designed to withstand

prolonged direct exposure to the elements. Accordingly, upon application of this product the outer roof should be installed without delay. Bradford Enviroseal Roof Tile should be installed with the green side facing outwards. In roofing applications, CSR Bradford Insulation recommends using a minimum sag of 40mm deep between the rafters, except at the eaves. To ensure effective performance and satisfactory lifespan, radiant barriers such as Enviroseal must be installed with a minimum airspace of at least 20mm on the reflective face. For specialised applications please refer to your nearest Bradford Insulation office.

ENVIROSEAL™ ROOF TILE

Physical Properties

Classification in accordance with AS/NZ 4200.1 unless otherwise stated. **When tested to 1530.2, it complies to requirements set out for extreme bush fire attack category BCA clause 3.7.4.3.

	Pitched Roof Tile	
	Summer	Winter
	R _T 1.6	R _T 0.9

Thermal Performance

The thermal performance of reflective insulation varies according to the direction of the heat flow. The following tables provides total R values for common systems in accordance with AS4859.1:2002 Materials for the Thermal Insulation of Buildings.

- Emittance of reflective foil surfaces 0.05 or less
- Temperature difference 6°C for heat flow in and 12°C for heat flow in
- EnviroSeal installed under the battens, above the rafters, reflective surface facing down, sagged ≥40mm
- Emittance of antiglare surface 0.86

Classifications

Duty	Table 1 AS/NZS 4200.1:1994	Heavy
Vapour Barrier	ASTM E96	Medium
Emittance	AS/NZS 4201.5	Reflective
Water Barrier	AS/NZS 4201.4	High
Absorbency	AS/NZS 4201.6	Unclassified
Resistance to Dry De-Lamination	AS/NZ 4201.1	Pass
Resistance to Wet De-Lamination	AS/NZ 4201.2	Pass
Shrinkage	AS/NZ 4201.3	≤0.5%
Tensile Strength	AS 1301.448	
Machine Direction(kN/m)		(Min 12.5) 14.5
Lateral Direction(kN/m)		(Min 7.5) 8.8
Edge Tear Resistance	TAPPI T470	
Machine Direction (N)		(Min 80) 523
Lateral Direction (N)		(Min 80) 320
Folding Endurance	AS 1301.423	
Machine Direction		>2.00
Cross Direction		>1.70
Fire Resistance		
Spread Factor	AS 1530 Part 2	0
Speed Factor	AS 1530 Part 2	0
Heat Factor	AS 1530 Part 2	1
Flammability Index**	AS 1530 Part 2	1

Bradford™
for smarter environments

CSR Bradford Insulation

55 Stennett Rd, Ingleburn NSW 2565 Australia.

Telephone (02) 9765 7000 **Facsimile** (02) 9765 7002

www.bradfordinsulation.com.au

CSR Bradford Insulation is a business division of CSR Building Products Limited ABN 55 008 631 356

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford Insulation. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the Bradford website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.